

Diesel Exhaust Fluid (DEF) Transfer Hose

Diesel Exhaust Fluid (DEF) Transfer Hose

Novaflex 4203BE is a 200 psi working pressure rated hose specifically designed to transfer DEF fluids. This suction and discharge hose has an EPDM construction designed to be resistance to the effects of the media transferred. This hose is flexible and excellent for reel applications.

Construction

Tube: Specially Formulated EPDM
 Reinforcement: Plies of tire cord & helix wire
 Cover: Black or Blue EPDM
 Length: 50' & 100' Plain ends / Boxed
 Temperature Range: -40°F to 210°F
 Branding - DEF Hose, 4203BE, 200 psi WP, 210°
 Max Temp., Urea Fluid



Part No.	Hose Colour	ID"	OD"	WP psi	Vacuum HG	Weight/Lbs/ft	Bend Radius"
4203BE-00750-00	Black	.075	1.25	200	Full	0.48	2.5
4203BE-01000-00	Black	1	1.5	200	Full	0.6	3
4203BE-00750-00	Blue	.075	1.25	200	Full	0.48	2.5
4203BE-01000-00	Blue	1	1.5	200	Full	0.6	3

All hose and duct manufactured by Novaflex are warranted to be free from all defects in material and workmanship. It is impossible to test Novaflex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end user's responsibility to test all Novaflex hose and duct under conditions that duplicate the service conditions prior to installation. Due to continuous improvements, technical data subject to change without notice.

Rev 04.10

Indianapolis, IN
Haw River, NC
Berlin, NJ
Ajax, ON

Tel 317.334.1444 Fax 317.334.1535 800.526.6288
 Tel 336.578.2161 Fax 336.578.5554 800.334.4270
 Tel 856.768.2275 Fax 856.768.2385 800.225.0215
 Tel 905.686.5200 Fax 905.686.8349

NOVAFLEX®
 PROVIDING HOSE & DUCT SOLUTIONS
 Email: sales@novaflex.com
 Website: www.novaflex.com