

# Novaflex

## Material Handling Hose

### Novaflex 5016 (Vacuum Only)

#### Material Handling Hose 1/4" Gum Tube

Heavy duty material handling hose designed for portable and central industrial vacuum equipment as well as truck mount applications. The 1/4" abrasion resistant tube is designed to resist cutting, tearing and wear from abrasive media. The heavy helix wire is designed to resist kinking and crushing as well as handle full vacuum. (Ground using helix wire to make static conductive.)

#### Construction:

Tube: 1/4" tan gum

Reinforcement: Plies of fabric with helix wire.

Cover: SBR Black Corrugated

Length: 50 ft. Ends: Plain or soft cuffs.

Temperature Range: -40°F to +140°F

**Novaflex 5016YG** = Yellow Novaware tube  
superior abrasion resistance



Part No.	I.D.	O.D.	MBR (in)	VAC (Hg)	WT LBS/FT
5016BG-02500-00	2½	3.38	9	29"	2.0
5016BG-03000-00	3	3.88	12	29"	2.2
5016BG-04000-00	4	4.88	24	29"	3.0
5016BG-06000-00	6	6.88	36	29"	4.1
5016BG-08000-00	8	8.88	48	17"	7.2
5016BG-10000-00	10	10.88	60	9"	9.0
5016BG-12000-00	12	12.88	72	9"	11.4

It is impossible to test NovaFlex hose and duct under all conditions to which they might be subjected in the field. It is therefore the buyer and/or end users' responsibility to test all NovaFlex hose and duct under conditions that duplicate the service conditions prior to installation. Always consult the Novaflex Chemical Resistance Chart to verify chemical compatibility. (See: [www.novaflex.com](http://www.novaflex.com)). Due to continuous improvements, technical data is subject to change without notice.

ver 01.2016

**Indianapolis, IN** Tel 317.334.1444 Fax 317.334.1535 800.526.6288  
**Haw River, NC** Tel 336.578.2161 Fax 336.578.5554 800.334.4270  
**Berlin, NJ** Tel 856.768.2275 Fax 856.768.2385 800.225.0215  
**Ajax, ON** Tel 905.686.5200 Fax 905.686.8349

THE  
**NOVAFLEX**<sup>®</sup>  
GROUP

Email: [sales@novaflex.com](mailto:sales@novaflex.com)  
Website: [www.novaflex.com](http://www.novaflex.com)