

Novaflex

Novaflex 3257 Corrugated Low Temp Tank Truck Hose

Novaflex 3257 Corrugated Low Temp Tank Truck

A medium duty low temperature petroleum suction and transfer hose designed to be highly flexible with a hose cover that provides extra abrasion resistance to meet the demanding requirements of industry. Handles all grades of gasoline with aromatic contents to 55%.

Construction:

Tube: Black Nitrile

Reinforcement: Multiple plies polyester tire cord with helix

Cover: Corrugated Black oil resistant rubber

Length: 100 ft.

Temperature Range: -65°F to +180°F



Part No.	I.D.	O.D.	Plies	MBR (in)	VAC (Hg)	WP psi	WT LBS/FT
3257BT-01250-00	1¼	1.73	2	3	30"	150	0.71
3257BT-01500-00	1½	2.00	2	4	30"	150	0.84
3257BT-02000-00	2	2.50	2	4	30"	150	1.08
3257BT-02500-00	2½	3.07	2	6	30"	150	1.44
3257BT-03000-00	3	3.57	2	9	30"	150	1.85
3257BT-04000-00	4	4.67	2	14	30"	150	3.11

Due to continuous improvements, technical data subject to change without notice

01.2015

Indianapolis, IN Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Haw River, NC Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Berlin, NJ Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Ajax, ON Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP

Email: sales@novaflex.com
Website: www.novaflex.com