

Novaflex

Fluorinated Ethylene Propylene Tube, Suction & Discharge Hose

Novaflex 4600

Recommended for the transfer of those special products that require a hose tube with the highest level of chemical resistance.

FEP (Teflon type *) tube provides that extra margin of safety, with a white chemical resistant back-up rubber stock for high adhesions.

Applications

Tank Truck
Barge Loading
Storage tank transfer
In-plant applications requiring flexibility and durability

Product Specifications

Tube: FEP
Reinforcement: Multiple plies of synthetic, high strength textile with helix wire
Cover: Blue EPDM cover
Temperature: -40° to +300°F (-40°C to +149° C) normal service.
(This rating is dependent on chemical conveyed)
Branding: White Mylar brand - FEP Tube, Suction & Discharge Hose, WPXX
Couplings: Use only permanently attached couplings
Non-stock orders: Other color hose covers (red, green, white & gray) are available and require a 400 ft. order per ID
Meets or exceeds the requirements of FDA & USDA under 21 CFR 177, 1550, 3-A sanitary standards 20-15.



Part No	ID	OD	Plies	MBR	Vacuum	WP	WT
4600CF-00500-00	½	0.96	2	3	29	500	0.30
4600CF-00750-00	¾	1.2	2	3.5	29	500	0.45
4600CF-01000-00	1	1.46	2	4.0	29	450	0.57
4600CF-01500-00	1½	1.95	2	8.5	29	350	0.80
4600CF-02000-00	2	2.57	2	10	29	300	1.42
4600CF-03000-00	3	3.69	2	25	29	200	2.32

Due to continuous improvements technical data subject to change without notice

Berlin, NJ
Indianapolis, IN
Haw River, NC
Ajax, ON

Tel 856.768.2275 Fax 856.768.2385 800.225.0215
Tel 317.334.1444 Fax 317.334.1535 800.526.6288
Tel 336.578.2161 Fax 336.578.5554 800.334.4270
Tel 905.686.5200 Fax 905.686.8349

THE
NOVAFLEX
GROUP



Email: sales@novaflex.com
Website: www.novaflex.com